



NOTES:

- A. TANK, 30 GAL CAPACITY, POLYTHYLENE, WITH HINGED TOP, SS ATTACHMENT HARDWARE,
- B. PUMP, DIAPHRAGM METERING, MANUAL OUTPUT ADJUSTMENT, WORM GEAR DRIVEN, MODEL NO. JR102A
MOTOR: 1/4 HP, 1,725 RPM, TEFC, 1/50/120-240
CAPACITY: 4 GPH, UP TO 150 PSI
MATERIALS OF CONSTRUCTION:
WETTED END: PVC
DIAPHRAGM AND VALVE SEATS: NEOPRENE
VALVE BALLS: 316 SS
- C. PUMP SUPPORT: (2) 2" x 2" X 1/8" CS ANGLE, FASTENED TO TANK TOP W/ SS HARDWARE
- D. FLOOR SUPPORT (2) 2" X 2" X 1/8" CS ANGLE, WITH 2" X 1/8" CS BAR TOP AND BOTTOM PLATE, WELDED ASSEMBLY, PAINT: GREY ACRYLIC ENAMEL, TO BE FASTENED TO PUMP SUPPORTS AND FLOOR
- E. FOOT VALVE, PVC, WITH FILTER SCREEN INSTALLED IN PUMP SUCTION WITH 1/4" PVC PIPING

DISTRIBUTOR:

MADDEN MANUFACTURING, INC. ELKHART, IN	
CHEMICAL FEED SYSTEM MODEL NO. TE501	
DATE: 1/12/98 REV. NO. 0	XXX