



NOTES:

- A. TANK, 55 GAL CAPACITY, POLYTHYLENE, WITH HINGED TOP, SS ATTACHMENT HARDWARE, TWO 3/8" PVC BULKHEAD FITTING FOR PUMP SUCTION AND PRV PIPING INSTALLATION, P/N TF302
- B. MIXER, P/N AA103A, 1,725 RPM, 1/4 HP 1/60/115, TEFC MOTOR, 1/2" X 30" SS SHAFT WITH 4" SS PROP, MOUNTED TO MIXER STAND
- C. PUMP, DIAPHRAGM METERING, MANUAL OUTPUT ADJUSTMENT, WORM GEAR DRIVEN, MODEL NO. MF110A
MOTOR: 1/2 HP, 1,725 RPM, TEFC, 1/60/115-230
CAPACITY: 10 GPH, UP TO 150 PSI
MATERIALS OF CONSTRUCTION: CAST IRON SOLUTION HEAD, NEOPRENE DIAPHRAGM, 316 SS VALVE BALLS
- D. PLATFORM, 26" x 36": 11 GA CS TOP, WITH 2" X 2" X 1/8" ANGLE LEGS, WITH FOOT PADS, INCL VERTICAL MIXER MOUNTING STAND, GREY ACRYLIC ENAMEL FINISH, P/N TF202
- E. ANCHOR BOLT PATTERN: (4) 1/2" HOLES ON 32.5" X 22.5" PATTERN
- F. SUCTION PIPING: 3/8" PVC VALVE WITH 1/2" Y-STRAINER, 3/8" REINFORCED PVC TUBING WITH PVC HOSE BARBS AND SS HOSE CLAMPS, P/N TF350
- G. RELIEF VALVE AND PIPING: 316 SS PRV, SET AT ___ PSI, INSTALL IN TEE IN PUMP DISCHARGE CONNECTION, 3/8" NYLON REINFORCED PVC TUBING RETURN LINE TO TANK
- H. TANK STOP, 3 REQ'D, 1.5" X 1.5" CS ANGLE

DISTRIBUTOR:

MADDEN MANUFACTURING, INC.
ELKHART, IN

CHEMICAL FEED SYSTEM
MODEL NO. TE504

DATE: 10/30/00

TE504